



# JHPV TECH



WWW.JHPVTECH.COM

## JH-R126FM 360~380W

**22% Efficiency**

360~380W 126 pcs

P-TYPE Full Black monofacial



**15 Years**  
Material & Craft  
Quality  
Assurance

**30 Years**  
84.8% Output  
Power  
Guarantee


### KEY FEATURES HIGHLIGHTS



Mono MBB half cut  
Original European Parts



EU Standard  
European Quality  
Control



PID Resistance  
High stability and torsion  
free with Wave Shape

### PRODUCT CERTIFICATIONS



Production process  
reliability test  
electro-luminance  
inspection



AR coating  
tolerance and lower  
resistive loss



Excellent Durability  
resistant to salt mist, ammonia,  
dust and sand, snail trail.



Reduce BOS cost  
increase ROI  
Low temp coefficient  
(PMax) for higher output



Wide Applications  
Durability against Extreme  
Environmental Conditions



Lower Losses  
Multi Busbar Technology for  
better Light trapping

# JH-R126FM 360~380W



**JHPV TECH**

## Electrical parameters at Standard Test Conditions (STC\*) & Nominal Operating Cell Temperature (NOCT\*)

| Module Type                                      | 360W / 270W   | 365W / 274W   | 370W / 278W   | 375W / 282W   | 380W / 286W   |
|--|---------------|---------------|---------------|---------------|---------------|
| Test Environment                                 | STC / NOCT    | STC / NOCT    | STC / NOCT    | STC / NOCT    | STC / NOCT    |
| Power output tolerances P <sub>max</sub> (W)     | (0,+5)        | (0,+5)        | (0,+5)        | (0,+5)        | (0,+5)        |
| Module efficiency(%)                             | 20.40         | 20.70         | 21.00         | 21.20         | 21.50         |
| Voltage at P <sub>max</sub> V <sub>mpp</sub> (V) | 34.70 / 32.60 | 34.90 / 32.80 | 35.10 / 33.00 | 35.30 / 33.20 | 35.50 / 33.40 |
| Current at P <sub>max</sub> I <sub>mp</sub> (A)  | 10.37 / 8.28  | 10.46 / 8.35  | 10.54 / 8.42  | 10.62 / 8.49  | 10.70 / 8.56  |
| Open-circuit voltage V <sub>oc</sub> (V)         | 42.40 / 39.70 | 42.60 / 39.90 | 42.80 / 40.10 | 43.00 / 40.30 | 43.20 / 40.50 |
| Short-circuit current I <sub>sc</sub> (A)        | 10.94 / 8.84  | 11.02 / 8.91  | 11.10 / 8.98  | 11.18 / 9.05  | 11.26 / 9.12  |

\*STC: 1000 W·m<sup>-2</sup> irradiance, 25°C cell temperature, AM 1.5 spectrum according to EN 60904-

\*NOCT: open-circuit module operation temperature at 800 W·m<sup>-2</sup> irradiance, 20°C ambient temperature, 1 m·s<sup>-1</sup> wind speed.

## GENERAL CHARACTERISTICS

Dimensions (L / W / H) 1840 mm / 1040mm / 2.5 mm

Weight 5.7 kg

## PACKAGING SPECIFICATIONS

Number of modules per pallet 46

Number of pallets per 40' container 24

## THERMAL CHARACTERISTICS

|   |      |        |        |
|---|------|--------|--------|
| Nominal operating cell temperature          | NOCT | °C     | 43 ± 2 |
| Temperature coefficient of P <sub>max</sub> | γ    | % / °C | -0.36  |
| Temperature coefficient of V <sub>oc</sub>  | β    | % / °C | -0.28  |
| Temperature coefficient of I <sub>sc</sub>  | α    | % / °C | 0.06   |

\*NOCT: open-circuit module operation temperature at 800 W·m<sup>-2</sup> irradiance, 20°C ambient temperature, 1 m·s<sup>-1</sup> wind speed.

## OPERATING CONDITIONS

Max. system voltage 1500 Vdc

Max. series fuse rating\* 18 A

Operating temperature range - 40°C to 85°C

Max. static load, front (e.g., snow) 5400 Pa

Max. static load, back (e.g., wind) 2400 Pa

Max. hailstone impact (diameter/velocity) 25 mm / 23 m·s<sup>-1</sup>

\*DO NOT CONNECT FUSE IN COMBINER BOX WITH TWO OR MORE STRINGS IN PARALLEL CONNECTION.

## CONSTRUCTION MATERIALS

Cell ( material / quantity ) monocrystalline silicon / 6 x 21


Glass (material) low-iron tempered glass

Frame (material) anodized aluminum alloy

Junction box (type / protection degree) 3 bypass diodes / ≥ IP68

Cable (length / cross-sectional area) ± 300 mm or customized length / 4 mm<sup>2</sup>

## BACK VIEW (Units: mm)



SECTION A-A



Warning: Read the Installation and User Manual in its entirety before handling, installing and operating Solar modules.



**NINGBO JING HONG ENERGY TECHNOLOGY CO., LTD.**

Email: Sales@jhpvtech.com

Web: <http://jhpvtech.com>

Address: No. 1 Xinsi Road, Xinbei District, Changzhou City, Jiangsu Province, P.R. China

